

CLAIMS

We claim:

1 1. A computer-implemented method for routing calls from at least one
2 caller to a subscriber of telecommunications services, wherein at least one call from the
3 caller is routed from a local telecommunications network to a distant central
4 telecommunications server, wherein the local telecommunications network includes a local
5 dialable network that differs from a local dialable network to which the central
6 telecommunications server is associated, the method comprising:

7 at a local controller coupled to and associated with the local
8 telecommunications network, receiving from the local telecommunications network an
9 incoming call from a calling number associated with a caller, to a called number associated
10 with the subscriber;

11 at the local controller, locally storing at least the called number associated with
12 the caller;

13 at the local controller, initiating a 1-800 call to the central telecommunications
14 server over a 1-800 network via the local telecommunications network;

15 at the local controller, transferring the called number to the central
16 telecommunications server via the 1-800 call over the 1-800 network;

17 at the central telecommunications server, receiving the calling and called
18 numbers and retrieving a subscriber profile based on the called number, wherein the
19 subscriber profile is associated with the subscriber and identifies subscriber defined call
20 routing preferences;

21 at the central telecommunications server, receiving the incoming call; and

22 at the central telecommunications server, routing the incoming call based on at
23 least one subscriber defined call routing preference in the retrieved subscriber profile.

1 2. The method of claim 1 wherein locally storing includes storing the
2 calling number, wherein transferring the called number includes transferring to the central
3 telecommunications server the called and calling numbers in available ISDN fields in the 1-
4 800 call, and wherein the method further comprises:

5 at the central telecommunications server, providing a confirmation
6 message to the local controller, wherein the confirmation message is provided over the
7 Internet;

8 at the central telecommunications server, providing the incoming call to
9 the local controller;

10 at the local controller, placing a local call over the local dialable
11 network to the subscriber; and

12 at the local controller, connecting the incoming call with the local call.

1 3. The method of claim 1 wherein the central telecommunications server
2 and local controller are coupled to a second 1-800 network, and wherein the method further
3 comprises:

4 at the central telecommunications server, providing a first error message
5 to the local controller;

6 at the local controller, providing the dialing number to the central
7 telecommunications server as in-band signaling in response to the first error message;

8 at the central telecommunications server, providing a second error
9 message to the local controller;

10 at the local controller, initiating another 1-800 call to the central
11 telecommunications server over the second 1-800 network in response to the second
12 error message;

13 at the central telecommunications server, providing the incoming call to
14 one of a plurality of local controllers;

15 at the one local controller, placing a local call to the subscriber; and

16 at the one local controller, connecting the incoming call with the local
17 call.

1 4. An apparatus for routing calls for a subscriber from a local
2 telecommunications network to a distant central telecommunications server, the apparatus
3 comprising

4 a memory,
5 a computer coupled to the memory, and
6 a telecommunications call handling subsystem coupled between the local
7 telecommunications network and the computer, wherein the computer and call handling
8 subsystem are configured to:

9 receive a call from a first number to a second number associated with
10 the subscriber; store in the memory at least the second number; initiate a 1-800 call to
11 the central telecommunications server over a 1-800 network via the local
12 telecommunications network; and transfer at least the second number to the central
13 telecommunications server via the 1-800 call over the 1-800 network.

1 5. The apparatus of claim 4 wherein transferring at least the second
2 number includes transferring to the central telecommunications server the called and calling
3 numbers in ISDN fields in the 1-800 call, and wherein the computer and call handling
4 subsystem are further configured to:

5 provide the second number to the central telecommunications server as
6 in-band signaling in response to a first error message received from the central
7 telecommunications server;

8 initiate another 1-800 call to the central telecommunications server over
9 a second 1-800 network in response to a second error message received from the
10 central telecommunications server; and

11 connect the call with the 1-800 call in response to an acknowledgement
12 message received from the central telecommunications server.

1 6. The apparatus of claim 4 wherein the computer and call handling
2 subsystem are further configured to:

3 receive a routing message from the central telecommunications server;

4 place a local call over the local dialable network to the subscriber based
5 on the received routing message; and
6 connect the call with the local call.

1 7. The apparatus of claim 4 wherein the computer is further coupled to the
2 Internet, and wherein the computer and the call handling subsystem are further configured to:

3 provide a first message over the Internet to the central
4 telecommunications server, wherein the first message is provided in response to the
5 call;

6 receiving a second message central telecommunications server over the
7 Internet, from central telecommunications server.

1 8. The apparatus of claim 4 wherein transferring at least the second
2 number includes transferring to the central telecommunications server the calling number as
3 DTMF signaling.

1 9. The apparatus of claim 4 wherein transferring at least the second
2 number includes transferring to the central telecommunications server the called number in
3 an available ISDN field in the 1-800 call.

1 10. The apparatus of claim 4 wherein the apparatus is coupled to a second
2 1-800 network, and wherein the computer and call handling subsystem are further configured
3 to:

4 initiate a 1-800 call to the central telecommunications server over the
5 second 1-800 network in response to a message received from the central
6 telecommunications server.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

11. The apparatus of claim 4 wherein the apparatus is coupled to a second 1-800 network and a second central telecommunications server, and wherein the computer and call handling subsystem are further configured to:

initiate a 1-800 call to the second central telecommunications server over the second 1-800 network in response to a switch message or lack of an acknowledgment message from the central telecommunications server.

12. The apparatus of claim 4 wherein the computer and call handling subsystem are further configured to:

provide voice scripts to the received call; and
receive and store in the memory a voice message.

13. The apparatus of claim 4 wherein the computer and call handling subsystem are further configured to:

receive and store in the memory a voice message based on the call; and
forward to the central telecommunications server the stored voice message.

14. The apparatus of claim 4 wherein a caller places the call from the first number, and wherein the computer and call handling subsystem are further configured to:

provide voice scripts to the caller;
initiate the 1-800 call to a first 1-800 number based on a first input signal received from the caller; and
initiate another 1-800 call to another 1-800 number based on a second input signal received from the caller.

1 15. The apparatus of claim 4 wherein the computer and call handling
2 subsystem are coupled to the Internet and are further configured to:

3 provide an alert message to the subscriber over the Internet based on the
4 received called; and

5 receive a call disposition message from the subscriber that indicates how
6 the received call is to be routed.

1 16. The apparatus of claim 4 wherein transferring at least the second
2 number includes transferring to the central telecommunications server the called number in
3 an in-band signal associated with the 1-800 call.

1 17. The apparatus of claim 4 wherein transferring at least the second
2 number includes transferring to the central telecommunications server the called number in
3 an out-of-band signal associated with the 1-800 call during set up of the 1-800 call.

1 18. The apparatus of claim 4 wherein the computer is coupled to a computer
2 network, and wherein transferring at least the second number includes transferring to the
3 central telecommunications server over the computer network the called number in an
4 Internet Protocol (IP) message.

1 19. The apparatus of claim 4 wherein the computer and call handling
2 subsystem are further configured to:

3 receive a routing message from the central telecommunications server;

4 place another 1-800 call to another apparatus based on the received
5 routing message, wherein the another apparatus is substantially similar to the
6 apparatus; and

7 connect the call with the another 1-800 call.

1 20. An apparatus for routing calls for a subscriber from a first Private
2 Branch Exchange ("PBX") network to a distant central telecommunications server, the
3 apparatus comprising

4 a memory,
5 a computer coupled to the memory, and
6 a telecommunications call handling subsystem coupled between the PBX
7 network and the computer, wherein the computer and call handling subsystem are configured
8 to:

9 receive a call from a first number to a second number associated with
10 the subscriber; store in the memory at least the first number; initiate a dial-up call to
11 the central telecommunications server over a dial-up network via the local
12 telecommunications network; transfer at least the first number to the central
13 telecommunications server via the dial-up call over the dial-up network, and transfer
14 the received call to the central telecommunications server, wherein the central
15 telecommunications server is capable of routing the received call to a second PBX.

1 21. An apparatus for routing calls for a subscriber from a local
2 telecommunications network to a distant central telecommunications server, the apparatus
3 comprising:

4 receiving means for receiving, from the local telecommunications network, a
5 call from a first number, to a second number associated with the subscriber;

6 storage means, coupled to the receiving means, for locally storing at least the
7 second number;

8 call initiating means, coupled to the storage means, for initiating a 1-800 call to
9 the central telecommunications server over a 1-800 network via the local telecommunications
10 network; and

11 call transferring means, coupled to the call initiating means, for transferring at
12 least the first number to the central telecommunications server via the 1-800 call over the 1-
13 800 network.

1 22. An apparatus for routing calls for a subscriber from a local controller
2 coupled to a local telecommunications network, the apparatus comprising

3 a memory,

4 a computer coupled to the memory, and

5 a telecommunications call handling subsystem coupled between a 1-800
6 network and the computer, wherein the computer and call handling subsystem are configured
7 to:

8 receive a 1-800 call over a 1-800 network from the local controller
9 based on a call received by the local controller from a first number to a second
10 number associated with the subscriber; receive the first and second numbers from the
11 local controller via the 1-800 call over the 1-800 network; and determine routing of
12 the call based on the received first and second numbers.

1 23. The apparatus of claim 22 wherein the telecommunications call handling
2 subsystem is coupled to a second 1-800 network, and wherein the computer and call handling
3 subsystem are further configured to:

4 instruct the local controller to place at least some 1-800 calls over the
5 second 1-800 network.

1 24. The apparatus of claim 22 wherein the computer gathers metrics based
2 on calls received from the 1-800 network.

1 25. The apparatus of claim 22 computer and call handling subsystem are
2 coupled to the Internet and are further configured to:

3 provide a locator message to another local controller over the Internet,
4 based on the call received by the local controller; and

5 receive an indication message over the Internet from the another local
6 controller of whether the subscriber is within a local telecommunications network
7 associated with the another local controller.

1 26. A computer-readable medium whose contents cause an apparatus to
2 route calls for a subscriber from a local telecommunications network to a distant central
3 telecommunications server, comprising:

4 receiving, from the local telecommunications network, a call from a first
5 number, to a second number associated with the subscriber;

6 locally storing at least the second number;

7 initiating a dial-up call to the central telecommunications server over a dial-up
8 network via the local telecommunications network; and

9 transferring at least the second number to the central telecommunications
10 server via the dial-up call over the dial-up network.

1 27. The computer-readable medium of claim 26 wherein the computer-
2 readable medium is a logical node in a computer network receiving the contents.

1 28. The computer-readable medium of claim 26 wherein the computer-
2 readable medium is a computer-readable disk.

1 29. The computer-readable medium of claim 26 wherein the computer-
2 readable medium is a data transmission medium transmitting a generated data signal
3 containing the contents.

1 30. The computer-readable medium of claim 26 wherein the computer-
2 readable medium is a memory of a computer.

1 31. A method for routing calls for a subscriber from a local
2 telecommunications network to a central telecommunications server, wherein a long distance

3 telephone call is necessary to connect calls from the local telecommunications network to the
4 central telecommunications server, the method comprising:

5 receiving a request to establish a 1-800 call over a 1-800 network from a local
6 controller based on a call received by the local controller from a first number to a second
7 number associated with the subscriber, wherein the 1-800 network is coupled to the local
8 telecommunications network;

9 establishing the 1-800 call to the central telecommunications server and
10 providing the first and second numbers to the central telecommunications server via the 1-
11 800 call over the 1-800 network, wherein at least the second number is provided: in an in-
12 band signal with the 1-800 call, in an available field in an out-of-band signal during
13 establishment of the 1-800 call, or in an Internet Protocol ("IP") message provided to the
14 central telecommunications server over a separate IP data network.

1 32. The method of claim 31, further comprising, receiving instructions to
2 establish 1-800 calls to another central telecommunications server when requests to establish
3 1-800 calls are received from the local controller.

1 33. A computer-readable medium containing a data structure for use with a
2 local controller that routes calls received for a subscriber, wherein the calls are received from
3 a local telecommunications network, the data structure comprising:

4 a first number field comprising a first server dial-up number associated with a
5 first central telecommunications server;

6 a first subscriber number field comprising a first subscriber dial-up number;
7 and

8 a second subscriber number field comprising a second subscriber dial-up
9 number, wherein the first and second subscriber dial-up numbers are associated with first and
10 second different call handling facilities of the subscriber, and wherein the local controller
11 receives calls to the subscriber via the local telecommunications network that are to be routed
12 to the first central telecommunications server or first or second facilities based on first,
13 second or third caller-provided instruction signals, respectively.

1 34. A method for routing calls for a subscriber from a local
2 telecommunications network to a distant central telecommunications server, the method
3 comprising:

4 identifying at least first and second dial-up networks associated with respective
5 first and second dial-up service providers, wherein the first and second dial-up service
6 providers are different;

7 selecting the first or second dial-up network based on at least one criterion;

8 receiving from the local telecommunications network, a call from a first
9 number, to a second number associated with the subscriber;

10 initiating a dial-up call to the central telecommunications server over the
11 selected dial-up network via the local telecommunications network; and

12 transferring at least the first number to the central telecommunications server
13 via the dial-up call over the selected dial-up network.

1 35. The method of claim 34 wherein the criterion is cost and the first dial-up
2 network and service provider are a 1-800 network and 1-800 service provider, respectively.

1 36. The method of claim 34 wherein the criterion is reliability.

1 37. The method of claim 34 wherein the criterion is load balancing between
2 the central telecommunications server and another central telecommunications server.

1 38. The method of claim 34, further comprising:

2 gathering metrics based on calls to the first and second dial-up networks; and
3 providing, for a fee, the gathered metrics.

1 39. The method of claim 34 wherein selecting the first or second dial-up
2 network comprises negotiating, via electronic message exchange, a lowest price between the
3 first and second dial-up service providers.